

RECLAIMED AMERICAN HARDWOODS - AMERICAN GOTHIC

Reclaimed Oak, Red Oak**, White Oak**, Hickory, Beech, Grey Elm, Maple, Chestnut, Red Elm, Cherry, Walnut & Autumn Woods

DENSITY

No limit on grain density

HEARTWOOD

No limit on combination of heartwood and sapwood

GRAIN

A mixture of flat-sawn and vertical grain

COLOR

No restriction on natural color variation

KNOTS

No limitation on sound knots. Surface defects resulting from chipped or broken knots will be present.

TEXTURE

Re-sawing and milling removes all but infrequent saw marks and previous wear patterns.

HOLES

Nail and other mechanical holes can be present and occasionally reach 3/8" in diameter. Surface defects from insect tracks and pin holes will be present at times in heavy concentrations.

DISCOLORATION

Ferrous staining from previous fasteners may be present.

CHECKS

Checks and crack allowed to 3/32" in widths less than 7".
In widths 7" and wider these sizes increase.

LENGTHS

2' - 12' is standard, 5' - 7' average

* Grading applies to flooring and boardstock, all material graded best face.

**This specification guarantees 90% of the called specie with an allowance of up to 10% of the other specie.

**PIONEER
MILLWORKS**

1180 COMMERCIAL DRIVE :: FARMINGTON NY 14425 :: (800) 951-9663

FAX (585) 924-9962 :: www.pioneermillworks.com :: jered@pioneermillworks.com